Tofil PULSE- 1 Arm



HIGH QUALITY EXTRACTION ARM

Durable extraction arms designed to provide best performance during extraction of fumes & dusts.

STATE OF THE ART EXTRACTION HOOD

Special designed extraction hood provide superior performance.

JET-PULSE AUTOMATIC CLEANING SYSTEM

Automatic jet-pulse cleaning system for continous operation and less frequent maintenance.

CLEANABLE CARTRIDGE FILTERS

Top quality and cleanable cartridge filters allow you long filter lifetime and lower cost of ownership

CONTROL & SIGNAL PANEL

Each device equipped with filter clog displaty, fan rotation direction display, ON/OFF switch and working hour counters.

GENERAL INFORMATION		
Filter Type	Cartridge	
Filter Media		
Standard	nanoBLEND FR	
Optional	polyMIGHT PTFE 65	
No of Cartridge Filters	2	
Total Filtation Area		
Standard	36 m²	
Optional	20 m²	
Filtration Efficiency		
Standard	F9 Class	
Optional	H13/H14 Class	

TECHNICAL INFORMATION		
Extraction Capacity	1.400 m³/h	
Dimensions (W x L x H)	890 x 810 x 1.760 mm	
Motor Power	1,1 kW - 3.000 rpm	
Power Supply	380 V / 50 Hz	
Noise Level	73 dB(a)	

ORDER NO		
3 m Inner Support Arm w/ nanoBLEND FR	TPULSE-13I-NB	
3 m Inner Support Arm w/ polyMIGHT PTFE 65	TPULSE-13I-PTFE	
3 m Outter Support Arm w/ nanoBLEND FR	TPULSE-130-NB	
3 m Outter Support Arm w/ polyMIGHT PTFE 65	TPULSE-130-PTFE	
4 m Outter Support Arm w/ nanoBLEND FR	TPULSE-140-NB	
4 m Outter Support Arm w/ polyMIGHT PTFE 65	TPULSE-140-PTFE	
SPARE PART ORDER NO		
nanoBLEND FR Filter	351/600/B135FR	
polyMIGHT PTFE 65 Filter	351/600/265PTFE	
3 m Flexible Hose	MF-3H-S	
4 m Flexible Hose	MF-4H-S	

