


Tofil PULSE - 2 Arms



HIGH QUALITY EXTRACTION ARM

Durable extraction arms designed to provide best performance during extraction of fumes & dusts.

STATE OF THE ART EXTRACTION HOOD

Special designed extraction hood provide superior performance.

JET-PULSE AUTOMATIC CLEANING SYSTEM

Automatic jet-pulse cleaning system for continuous operation and less frequent maintenance.

CLEANABLE CARTRIDGE FILTERS

Top quality and cleanable cartridge filters allow you long filter lifetime and lower cost of ownership

CONTROL & SIGNAL PANEL

Each device equipped with filter clog display, fan rotation direction display, ON/OFF switch and working hour counters.

GENERAL INFORMATION

Filter Type	Cartridge
Filter Media	
Standard	nanoBLEND FR
Optional	polyMIGHT PTFE 65
No of Cartridge Filters	2
Total Filtration Area	
Standard	36 m ²
Optional	20 m ²
Filtration Efficiency	
Standard	F9 Class
Optional	H13/H14 Class

TECHNICAL INFORMATION

Extraction Capacity	1.300 m ³ /h x 2
Dimensions (W x L x H)	890 x 810 x 1.760 mm
Motor Power	1,1 kW - 3.000 rpm
Power Supply	380 V / 50 Hz
Noise Level	75 dB(a)

ORDER NO

3 m Inner Support Arm w/ nanoBLEND FR	TPULSE-23I-NB
3 m Inner Support Arm w/ polyMIGHT PTFE 65	TPULSE-23I-PTFE
3 m Outer Support Arm w/ nanoBLEND FR	TPULSE-23O-NB
3 m Outer Support Arm w/ polyMIGHT PTFE 65	TPULSE-23O-PTFE
4 m Outer Support Arm w/ nanoBLEND FR	TPULSE-24O-NB
4 m Outer Support Arm w/ polyMIGHT PTFE 65	TPULSE-24O-PTFE

SPARE PART ORDER NO

nanoBLEND FR Filter	351/600/B135FR
polyMIGHT PTFE 65 Filter	351/600/265PTFE
3 m Flexible Hose	MF-3H-S
4 m Flexible Hose	MF-4H-S

