



HIGH QUALITY EXTRACTION ARM

Durable extraction arms designed to provide best performance during extraction of fumes & dusts.

STATE OF THE ART EXTRACTION HOOD

Special designed extraction hood provide superior performance.

CLEANABLE CARTRIDGE FILTERS

Top quality and cleanable cartridge filters allow you long filter lifetime and lower cost of ownership

CONTROL & SIGNAL PANEL

Each device equipped with filter clog display, fan rotation direction display, ON/OFF switch and working hour counters.

GENERAL INFORMATION

Filter Type	Cartridge
Filter Media	
Standard	nanoBLEND FR
Optional	polyMIGHT PTFE 65
No of Cartridge Filters	1
Total Filtration Area	
Standard	18 m ²
Optional	10 m ²
Filtration Efficiency	
Standard	F9 Class
Optional	H13/H14 Class

TECHNICAL INFORMATION

Extraction Capacity	1.200 m ³ /h
Dimensions (W x L x H)	660 x 805 x 1.210 mm
Motor Power	0,75 kW - 3.000 rpm
Power Supply	380 V / 50 Hz
Noise Level	72 dB(a)

ORDER NO

3 m Inner Support Arm w/ nanoBLEND FR	TM-13I-NB
3 m Inner Support Arm w/ polyMIGHT PTFE 65	TM-13I-PTFE
3 m Outer Support Arm w/ nanoBLEND FR	TM-13O-NB
3 m Outer Support Arm w/ polyMIGHT PTFE 65	TM-13O-PTFE
4 m Outer Support Arm w/ nanoBLEND FR	TM-14O-NB
4 m Outer Support Arm w/ polyMIGHT PTFE 65	TM-14O-PTFE

SPARE PART ORDER NO

nanoBLEND FR Filter	351/600/B135FR
polyMIGHT PTFE 65 Filter	351/600/265PTFE
3 m Flexible Hose	MF-3H-S
4 m Flexible Hose	MF-4H-S

