Tofil^{PRO} - 1 Arm



HIGH QUALITY EXTRACTION ARM

Durable extraction arms designed to provide best performance during extraction of fumes & dusts.

STATE OF THE ART EXTRACTION HOOD

Special designed extraction hood provide superior performance.

CLEANABLE CARTRIDGE FILTERS

Top quality and cleanable cartridge filters allow you long filter lifetime and lower cost of ownership

CONTROL & SIGNAL PANEL



Each device equipped with filter clog displaty, fan

ORDER NO

rotation direction display, ON/OFF switch and working hour counters.

548 B	
GENERAL INFORMATION	
Filter Type	Cartridge
Filter Media	
Standard	nanoBLEND FR
Optional	polyMIGHT PTFE 65
No of Cartridge Filters	1
Total Filtation Area	
Standard	24 m²
Optional	20 m ²
Filtration Efficiency	
Standard	F9 Class
Optional	H13/H14 Class

TECHNICAL INFORMATION	
Extraction Capacity	1.400 m ³ /h
Dimensions (W x L x H)	650 x 815 x 1.320 mm
Motor Power	1,1 kW - 3.000 rpm
Power Supply	380 V / 50 Hz
Noise Level	73 dB(a)

TPRO-13I-NB		
TPRO-13I-PTFE		
TPRO-130-NB		
TPRO-130-PTFE		
TPRO-140-NB		
TPRO-140-PTFE		
SPARE PART ORDER NO		
380/660/B135FR		
380/660/265PTFE		
MF-3H-S		
MF-4H-S		

